







Eaton's Type 2 Complete Home Surge Protection (CHSP) products are UL® 1449 3rd Edition Listed and provide the highest level of surge protection and safety.

Type 2 surge products are permanently connected devices that are installed on the load side of the service entrance overcurrent protective device.

Eaton's Surge Protective Devices (SPD):

- Include the industry's most complete line of products
- Provide superior protection for sensitive electronics
- Carry comprehensive warranty coverage

Choose From:

- · Factory mounted designs
- · Field installed options
- Universal products available to be mounted to any manufacturer's loadcenter
- Mounting accessories

Additional Protection:

Electrical surges can travel on your electrical, telephone and cable lines, and through your electronic equipment causing damage. CHSP Type 2 product line includes:

• Telephone and Cable SPDs

Surge Protection at the Service Entrance Panel

All products below are **HOLMES Approved** and provide AC Power Protection, LED Status Indication, a Limited Lifetime Warranty, and are suitable for indoor/outdoor applications when properly installed. Ratings include: UL 1449 3rd Edition Listed, cUL Listed, Voltage Protection Rating: 600V L - N, 1000V L - L, 800V N - G and 600V L - G, 120/240 Vac and 50/60 Hz.



CHSPT2ULTRA (BEST)

- 20kA (In) Nominal Discharge Current 1
- 108kA Surge Current Capacity Per Phase Rating 2
- *\$75,000 Warranty



CHSPT2MAX (BETTER)

- 10kA (In) Nominal Discharge Current
- 72kA Surge Current Capacity, Per Phase Rating
- *\$50,000 Warranty



CHSPT2MICRO (GOOD)

- 5kA (In) Nominal Discharge Current
- 36kA Surge Current Capacity, Per Phase Rating
- *\$25,000 Warranty

All products below are **HOLMES Approved**, UL/cUL Listed, offer a Limited Lifetime Warranty and are suitable for indoor cable or phone applications when properly installed.



CHSPCABLE

- · Protects 2 quad shield cables
- · Bi-directional cable
- 10kA Surge Current Capacity, Per Line
- 145V DC Breakdown Voltage
- *\$10,000 Warranty



CHSPTELE

- Protects 4 telephone lines
- 20kA Surge Current Capacity, Per Line
- 230V DC Breakdown Voltage
- Ring 90-120 Vac / Tone 48-52 Vdc
- *\$10,000 Warranty



CHSPT23PACK (Combo Pack)

- Protects AC Power, Cable and Telephone
- 3-Pack includes CHSPT2ULTRA, CHSPCABLE and CHSPTELE
- See individual product features for details





Eaton Corporation

Electrical Sector 1111 Superior Ave. Cleveland, OH 44114 United States 877-ETN-CARE (877-386-2273)

© 2012 Eaton Corporation All Rights Reserved Printed in USA Publication No. BR00414002E April 2012



- In: Nominal Discharge Current is the current that the device can withstand for 15 impulses.
- Surge Current Capacity: The maximum amount of surge current the device can shunt to ground during a surge event on one phase.
- Warranty amount is for connected equipment. For warranty details and product information visit, www.eaton.com/surgetrap.